

**15 YEARS  
OF PRODUCTS  
& SERVICE**

# HINDUSTAN ELECTRONICS

[www.hindustanrelay.com](http://www.hindustanrelay.com)

**SOLID  
STATE  
RELAYS &  
SENSORS**



## SINGLE PHASE SSR (RANGE 10A - 150AMP)

**DC/AC SSR & AC/AC SSR**

**Salient Features**

- Opto - Isolation 2500 VAC
- Compatible to TTL/CMOS
- LED For Status Indications
- Output NC Configuration For DC/DC SSR On Request
- Zero Voltage Turn - On/Random Turn-On
- Input Reverse Voltage Protection For DC Control
- Faster Switching Response
- Built - In Snubber
- Available In Eco Type

## PCB MOUNTING SSR (RANGE 2A - 7AMP)

**DC/AC SSR & DC/DC SSR**

**Salient Features**

- Opto - Isolation 2500 VAC
- Zero Voltage Turn - On/Random Turn-On
- Compatible to TTL/CMOS
- LED For Status Indications
- Input Reverse Voltage Protection For DC Control
- Output NC Configuration For DC/DC SSR On Request
- Faster Switching Response
- Built-In Snubber
- Available In Eco Type



## THREE PHASE SSR (RANGE 10A - 100AMP)

**DC/AC SSR & AC/AC SSR**

**Salient Features**

- Opto - Isolation 2500 VAC
- Zero Voltage Turn -On/Random Turn-On
- Input Reverse Voltage Protection For DC/AC SSR
- Built - In Snubber
- Input Control DC OR AC Voltage
- Load Current  
3 X 10A/16A/25A/40A/50A/60A/75A/100A
- Available in ECO type upto 16 AMP

## DC DC SSR (RANGE 2A - 100 AMP)

**Salient Features**

- Opto - Isolation
- MOSFET Output
- Reverse Polarity Protection
- Microsecond Switching
- Available in ECO type on request



## PHASE ANGLE CONTROL SSR (RANGE 10A - 50 AMP)

**Salient Features**

- Energy Saving
- Solid State Reliability
- Input 3 & 4 250 K at 480 VAC
- Full Wave Control
- Triac Full Wave AC



**E-mail : [hindustanrelay@gmail.com](mailto:hindustanrelay@gmail.com)**

**Website : [www.hindustanrelay.com](http://www.hindustanrelay.com)**

15 YEARS  
OF PRODUCTS  
& SERVICE

# HINDUSTAN ELECTRONICS

www.hindustanrelay.com

SOLID  
STATE  
RELAYS &  
SENSORS



## INPUT/OUTPUT SSR MODULES (2A - 5 AMP)

DC/AC SSR MODULES & DC/DC SSR MODULES  
Available With 4, 8,  
16 SSR Modules

## DUAL SSR (TWO SSR IN ONE PACKAGE)

### DC/AC SSR (RANGE 10A - 50 AMP)

#### Salient Features

- Opto - Isolation 2500 VAC
- Zero Voltage Turn - On/Random Turn-On
- TWO SSR IN ONE STANDARD PACKAGE



## SHORT CIRCUIT PROTECTED SSR

#### Salient Features

- Opto - Isolation 2500 VAC
- Zero Voltage Turn - On/Random Turn - On
- Built - In Snubber
- Output NO Configuration

## PROXIMITY SENSORS

### INDUCTIVE/CAPACITIVE Proximity Sensors

- AC/DC Type
- M8 TO M50 Available
- PNP/NPN OR NO/NC Logic
- Sensing Distance as per size



## Temp sensors

- RTD's / Thermo Copes
- Wire / Connector Types
- Class A / Class B Elements
- Head Types



FOR FURTHER DETAILS PL. CONTACT :

## HINDUSTAN ELECTRONICS

Plot No. PAP-122, Shahunagar, G-Block, MIDC,  
Chinchwad, Near KSB Chowk, Pune-411 019.  
Maharashtra, INDIA. Tel Fax : (020) 27111693  
Mob. : 9850555014, 9665642267

E-mail : [hindustanrelay@gmail.com](mailto:hindustanrelay@gmail.com)  
[hindustanelectronics15@gmail.com](mailto:hindustanelectronics15@gmail.com)

Website : [www.hindustanrelay.com](http://www.hindustanrelay.com)

AUTHORISED DEALER :